

H264 High Profile Decoder 2.0 on HDVICP2 and Media Controller Based Platform Data Sheet

FEATURES

- Supports all features of Main Profile(MP) and High Profile (HP)
- Supports resolutions up to 4320 x 4096
- Supports progressive, interlaced, Picture Adaptive Frame Field (PicAFF) and Macro-block Adaptive Frame Field (MBAFF) type picture decoding
- Supports multiple slices and multiple reference frames
- Supports CAVLC and CABAC decoding
- Supports all intra prediction and inter prediction modes
- Supports up to 16 MV per MB
- Supports frame based decoding
- Supports picture width and height (resolutions) greater than 64 pixels including all standard resolutions. In case of high resolution(Max Width or Max Height in create time parameters is more than 2048), the minimum supported picture width is 336 pixels.
- Tested for compliance with JM version 10.1 reference decoder
- Supports reference picture list reordering
- Supports PCM macroblock decoding
- Supports graceful exit and error reporting under error conditions
- Supports error concealment
- Supports parse header functionality
- Supports access to parsed Supplemental Enhancement Information (SEI) and Video Usability Information (VUI) data
- Supports memory management and control operations (MMCO)
- Supports gaps in frame number
- Supports skip functionality
- Supports dynamic change in resolution
- Supports configurable display delay for low delay applications
- Supports low DDR footprint in closed loop scenario
- Supports low latency features – sub frame level synchronization for input and output. Input data synchronization is based upon slices and fixed length of bit-stream and output data synchronization is based on MB rows.
- Supports decoding of one frame each of multiple channels in a single process call
- Supports dual YUV dump
- Limited support for decoding of Scalable Video Coding (SVC) streams
- Supports parsing of stereo SEI and frame packing SEI
- Supports decrypting of embedded watermark in closed loop scenario
- Supports decoding of only specific frame types requested by user. User can choose decoding of only I/IDR, IP or all frame types.
- The other explicit features that TI's H.264 Decoder supports are
 - eXpressDSP Digital Media (XDM IVIDDEC3) interface compliant
 - Multiple instances of the decoder can be run simultaneously
 - Supports booting of HDVICP2
 - Implements different power optimization schemes
 - Supports YUV 420 semi-planar color subsampling format
 - Independent of any operating system
 - Ability to get plugged in any multimedia frameworks (eg. Codec Engine, OpenMax, GStreamer, etc)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Description

H.264 is the latest video compression standard from the ITU-T Video Coding Experts Group and the ISO/IEC Moving Picture Experts Group. This H.264 Decoder is validated on HDVIPC2 and Media Controller based platform with code generation tools version 4.5.1 for HDVIPC2 processor and code generation tools version 5.0.3 for Media controller processor.

Performance and Memory Summary

This section describes the performance and memory usage of H.264 High Profile Decoder.

Table 1 Configuration Table

CONFIGURATION	ID
H.264 High Profile Universal Decoder: Resolutions up to 1920 x 1080	H264_DEC_001
H.264 High Profile Universal Decoder: Resolutions between 2048 x 2048 and 4320 x 4096	H264_DEC_002
H.264 High Profile Universal N-Channel Decoder: Resolutions up to 1280 x 720, 4 channels are decoded with the same input for all the channels	H264_DEC_003
H.264 High Profile Universal Decoder: Resolutions - 1920 x 1080 and 4096 x 4096 with decoding only I/IDR and IP frame types	H264_DEC_004
H.264 High Profile Universal Decoder: Resolutions - 1920 x 1080 and 4096 x 4096 with decoding only I/IDR frame types	H264_DEC_005

**Table 2 Cycles Information - Profiled on DM816x REV-A2 EVM with Code Generation Tools
Version 5.0.3**

CONFIGURATION ID	HDVICP2 PERFORMANCE STATISTICS (MEGA CYCLES PER SECOND) ⁽¹⁾		
	TEST DESCRIPTION ⁽²⁾	AVERAGE ⁽³⁾	PEAK ⁽⁴⁾
H264_DEC_001	mobcal_p640x360_1mbps_IPB_30fps.264	22.25	23.34
	akiyo_p640x480_100kbps_IPP_30fps.264	29.45	29.71
	lambo_p720x480_2mbps_IPB_30fps.264	30.52	31.54
	cvmpMot_i720x480_3mbps_IPB_30fps.264	32.30	36.76
	mov817_p1280x720_5mbps_IPB_30fps.264	71.79	73.88
	station_p1920x1080_7mbps_IPB_30fps.264	155.67	160.63
	station_i1920x1080_9mbps_IPB_30fps.264	160.63	166.87
H264_DEC_002	sample_p4096x2048_38mbps_IPB_30fps.264	621.78	632.20
	bbccrowded_i4096x2320_47mbps_IPB_30fps.264	705.79	730.83
	vqeghd1_src01_original_p4096x4096_25mbps_IPP_30fps.264	1239.75	1300.06
	airshow_p4320x2048_35mbps_IPB_30fps.264	676.93	731.52
H264_DEC_003	foreman_p352x288_512kbps_IPB_30fps_4Ch.264	48.66	50.71
	mobcal_p640x360_1mbps_IPB_30fps_4Ch.264	87.06	91.83
	akiyo_p640x480_100kbps_IPP_30fps_4Ch.264	112.66	113.81
	lambo_p720x480_2mbps_IPB_30fps_4Ch.264	117.97	121.61
	campMot_i720x480_3mbps_IPBB_30fps_4Ch.264	129.28	143.28
	mov817_p1280x720_5mbps_IPB_30fps_4Ch.264	285.25	296.23
H264_DEC_004	station_p1920x1080_12Mbps_IPP_30fps.264	156.88	163.62
	station_i1920x1080_16Mbps_IPP_30fps.264	164.25	168.56
	vqeghd1_csrc12_original_p4096x4096_30Mbps_IPP_30fps.264	1251.08	1300.76
	vqeghd1_csrc12_original_i4096x4096_44Mbps_IPP_30fps.264	1259.57	1305.34
H264_DEC_005	station_p1920x1080_9Mbps_III_30fps.264	164.05	164.15
	station_i1920x1080_12Mbps_III_30fps.264	169.32	169.41
	vqeghd1_csrc12_original_p4096x4096_76Mbps_III_30fps.264	1301.10	1301.29
	vqeghd1_csrc12_original_i4096x4096_98Mbps_III_30fps.264	1306.12	1306.35

- (1) Measured on DM816x REV-A2 EVM having Cortex-A8 @ 1GHz, HDVICP2 @ 533MHz, Media Controller @ 250 MHz, L3 interconnect @ 500 MHz and DDR2 @ 400 MHz and there could be a variation of around 1-2% in the numbers.
- a) Media Controller code is placed in cacheable memory region in DDR.
- b) No latency from system at process call and processing unit as frame (no sub-frame level communication) is assumed.
- c) All Luma 2D Video buffers of codec being in TILED_8 Bit Memory and all Chroma 2D Video buffers of codec being in TILED_16 Bit Memory
- (2) Cycles have been measured across process call.
- (3) Intra frame period is 30, number of slices per picture is 1, frame rate is 30 fps.
- (4) Average is computed based on worst case cycles having 2 extra output frame buffers.
- (5) Peak is based on worst case cycles having no extra output frame buffer. It is computed as peak among 30 frames.

Table 3 Memory Statistics of Media Controller - Generated with Code Generation Tools Version 5.0.3

CONFIGURATION ID	RESOLUTION	MEMORY STATISTICS ⁽¹⁾							TOTAL
		PROGRAM MEMORY	DATA MEMORY						
			INTERNAL	EXTERNAL ⁽²⁾				STACK	
				PERSISTENT ⁽³⁾			CONST		
				TILED8 (numBufs x Width x Height)	TILED16 (numBufs x Width x Height)	TILED PAGE / RAW	RAW		
H264_DEC_001	Level 3.0 – 720x480	20	0	0	0	2311	520	2	2853
	Level 4.1 – 720x480	20	0	0	0	5053	520	2	5595
	Level 4.1 – 1280x720	20	0	0	0	7704	520	2	8246
	Level 4.1 – 1920x1080	20	0	0	0	8679	520	2	9221
	Level 5.0 – 1920x1080	20	0	0	0	23596	520	2	24138
	Level 5.0 – 2048x2048	20	0	0	0	23687	520	2	24229
	Level 5.1 – 1920x1080	20	0	0	0	28569	520	2	29111
	Level 5.1 – 2048x2048	20	0	0	0	40327	520	2	40869
H264_DEC_002	Level 5.1 – 4096x2048	20	0	0	0	40327	520	2	40869
	Level 5.1 – 4096x4096	20	0	0	0	40327	520	2	40869
	Level 5.1 – 4320x4096	20	0	0	0	42511	520	2	43053
H264_DEC_004	Level 4.1 – 1920x1080	20	0	0	0	392	520	2	934
	Level 5.1 – 4096x4096	20	0	0	0	13702	520	2	14244
H264_DEC_005	Level 4.1 – 1920x1080	20	0	0	0	392	520	2	934
	Level 5.1 – 4096x4096	20	0	0	0	13702	520	2	14244

(1) All memory requirements are expressed in kilobytes (1 K-byte = 1024 bytes) and there might be rounding to next integer K-byte. Stack can be kept in internal/external memory, negligible performance impact can be observed in Media Controller cycles if it is placed in external memory.

(2) Codec's request of memory container can be over-riden by application, adhering to the below rules

- TILED PAGE can be overridden by RAW
- TILED8, TILED16 can be overridden by TILED PAGE, RAW
- TILED16 can be overridden by TILED8, RAW, TILED PAGE

However, in case of overriding of 2B and 2C, there can be some performance impact.

(3) Persistent memory is instance specific and does not include I/O buffers.

(4) For N-channel case, the persistent memory requirement (TILED PAGE/RAW) should be computed as the sum of the memory requirement for the individual channels.

Table 4 Split-up of Media Controller Internal Data Memory Statistics

CONFIGURATION ID	DATA MEMORY - INTERNAL ⁽¹⁾		
	SHARED		INSTANCE
	CONSTANTS	SCRATCH	
H264_DEC_001, H264_DEC_002, H264_DEC_003, H264_DEC_004, H264_DEC_005	0	0	0

(1) Internal memory refers to on chip memory. If the system doesn't have enough internal memory, then external memory can also be used. Memory requirements are expressed in kilobytes.

Notes

- I/O buffers:
 - Input buffer size = 1000 KB (average case for 1920x1088)
 - Output buffer size = 3441 KB (for 1920x1088 resolution)
- None of the buffers at input and output level is accessed by Media Controller processor hence the data should be valid in DDR (not in cache)
- Total data memory for N non pre-emptive instances = Constants + Runtime Tables + Scratch + N * (Instance + I/O buffers + Stack)
- Total data memory for N pre-emptive instances = Constants + Runtime Tables + N * (Instance + I/O buffers + Stack + Scratch)
- MAIL BOX FIFO #0 and #1 are used and user numbering for Media Controller as 2 and for HDVICP2 as 3 is assumed
- It is assumed that RTS library from ARM is available in system because few symbols like memcpy are used in codec
- All constants and Input/Output Buffers to decoder are assumed to be in VDMA addressable space in DDR

References

- ISO/IEC 14496-10:2005 Information technology -- Coding of audio-visual objects -- Part 10: Advanced Video Coding
- eXpressDSP Algorithm Interoperability Standard (TMS320 Algorithm Interface Standard)
- H.264 High Profile Decoder on HDVICP2 and Media Controller Based Platform User's Guide (Literature Number: SPRUGN9)

Glossary

Term	Description
Constants	Elements that go into .const memory section
Scratch	Memory space that can be reused across different instances of the algorithm
Shared	Sum of Constants and Scratch
Instance	Persistent-memory that contains persistent information - allocated for each instance of the algorithm

Acronyms

Acronym	Description
AIR	Adaptive Intra Refresh
CIF	Common Intermediate Format
CPB	Coded Picture Buffer
D1	SDTV image resolution (720x480)
QCIF	Quarter Common Intermediate Format
ISO	International Organization for Standardization
ITU	International Telecommunication Union
VDMA	Video Direct Memory Access
SDTV	Standard Definition Television
SEI	Supplemental Enhancement Information
VUI	Video Usability Information
XDAIS	eXpressDSP Algorithm Interface Standard
XDM	eXpressDSP Digital Media
VGA	Video Graphics Array (640x480 resolution)

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have not been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive & Transportation	www.ti.com/automotive
Communications & Telecom	www.ti.com/communications
Computers & Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energyapps
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics & Defense	www.ti.com/space-avionics-defense
Video & Imaging	www.ti.com/video

TI E2E Community e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright 2014, Texas Instruments Incorporated